



enoline elite 4

THE ENOLINE ELITE, IS THE NEW GENERATION OF ENOMATIC WINE SERVING SYSTEMS WITH IMPROVED TECHNOLOGU AND MONITORING CAPABILITIES, ADVANCED PRESERVATION AND REFRIGERATION, PRECISE PORTION CONTROL SERVINGS, COMPACT AND VERSATILE DESIGN, WITH CUSTOMIZABLE OPTIONS AND DIFFERENT COLORS. AIMED TO PROVIDE A NEW INTERACTIVE WINE SERVICE EXPERIENCE, THE ELITE IS THE PERFECT FIT FOR ANY CONTEMPORARY WINE HOSPITALITY ENVIRONMENT

## enoline

- **Available model:**

- **enoline 4 RT / CT** (4 bottles in a row)

The system has a dual temperature compartment managed separately from 6 to 18 °C (from 43 to 64 °F) in order to serve both red and white wines.

**Temperature setting:** from 6 to 18 °C (from 43 to 64 °F).

**Cooling system:** by refrigerator compressor.

- **Use and system activation:** the system can be used either behind the counter (without wine card) or self-service (with wine card).

**Gas supply:** food grade Nitrogen or Argon (cylinder or generator not included).

- **Volumes:** 1 or 3 configurable volumes with touch screen key display.
- **Display:** each position has an LCD graphic touch screen interactive display to monitor the dispenser's functions. A central LCD graphic screen supplies general information.
- **Materials:** stainless steel, prepainted steel, glass.
- **Colors and finishings:** In addition to the classic stainless steel finish, it is possible to choose from the following colors: "black elegance", "black elegance precious" (pistons, handles and spouts in gold finish) or RAL

customised colours ([www.ralcolor.com](http://www.ralcolor.com)).

**Lighting:** double LED. Light intensity can be set; it changes according to different functions.

- **Environment control:** a junction box performs a check on all external environment conditions (temperature, pressure, humidity) in order to auto-adjust the dispenser's efficiency.

This guarantees increased precision of pour volumes and better functionality of the refrigeration system.

**Nitrogen/Argon leak control:** a designated pressure control system highlights any gas leak directly on the display.

- **Bottles lifting system:** by electrical pistons that avoid using air or gas for bottle activation.
- **Positioning:** can be lined up on both sides, 10 cm (2") at rear and 25 cm (9,8") on the top needed; support furniture needed.
- **Wine card types:** chip card (SMART card) and RFID MIFARE (shared-use MAD system compatible). Finger print, magnetic stripe or bar code customizable upon request.

**Modules interfacing:** LAN network, TCP/IP protocol

model	L	H	D	weight	electrical requirements
enoline 4 TC	532 mm (21")	670 mm (26.4")	303 mm (11.9")	45 kg (99.2lbs)	100 V /220 V. - 250 W